

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 10/31/2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance

Trade name : Ethanol, abs. 100%, HPLC grade

EC Index-No. : 603-002-00-5
EC-No. : 200-578-6
CAS-No. : 64-17-5

REACH registration No : 01-2119457610-43

Product code : CL00.0529
Type of product : Pure substance

Formula : C2H6O

Synonyms : 1-hydroxyethane / absolute alcohol / absolute ethanol / alcohol 200 proof / alcohol

C2 / alcohol, absolute / alcohol, anhydrous / alcohol, dehydrated / algrain / anhydrol / anydrol / APEXA / bioethanol / BIO-Fire / cologne spirit / cologne spirits / ECO-Fire / ethanol / ethanol 200 proof / ethanol, absolute / ethicap / ethyl alcohol / ethyl alcohol, anhydrous / ethyl hydrate / ethyl hydroxide / ethylic alcohol / fermentation alcohol / grain alcohol / hydrated oxide of ethyl / IMS grades (=ethanol) / industrial alcohol / jaysol / jaysol S / methyl carbinol / methylated spirit (=ethanol) / molasses alcohol / neutral spirits / potable spirits / potato alcohol / proof spirits / rectified spiritus / SD alcohol 23-hydrogen /

silent spirit / spirit / spirit of wine / spirits of wine / tecsol / Tecsol C

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemical

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Chem-Lab nv Industriezone "De Arend" 2 Zedelgem - Belgium T +32 50 288320

info@chem-lab.be - www.chem-lab.be

1.4. Emergency telephone number

Emergency number : +32 50 28 83 20

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

EN (English) 1/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol, abs. 100%, HPLC grade	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	100	Flam. Liq. 2, H225

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink.

First-aid measures after inhalation

First-aid measures after skin contact First-aid measures after eye contact

First-aid measures after ingestion

: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

: Rinse with water. Take victim to a doctor if irritation persists.

: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

: Rinse mouth with water. Do not induce vomiting. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Respiratory difficulties. Central nervous system depression. Symptoms similar to those listed under ingestion.

Symptoms/effects after skin contact Symptoms/effects after eye contact : Slight irritation

: Redness of the eye tissue. Lacrimation. ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the eye tissue.

Symptoms/effects after ingestion

: AFTER INGESTION OF HIGH QUANTITIES: Risk of aspiration pneumonia. Red skin. Body temperature rise. Damp/clammy skin. Excited/restless. Accelerated heart action. Central nervous system depression. Dizziness. Narcosis. Headache. Drunkenness. Nausea. Vomiting. Disturbed motor response. Coordination disorders. Visual disturbances. Impaired concentration. Delusions. Disturbed sensation of pain. Disturbances of heart rate. Disturbances of consciousness. Tremor. Cramps/uncontrolled muscular contractions.

Dilated pupils.

Chronic symptoms

: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Gastrointestinal complaints. Enlargement/affection of the liver. Change in the haemogramme/blood composition. Cardiac and blood circulation effects. High arterial pressure. Impairment of the nervous system. Behavioural disturbances. Mental confusion. Disturbed tactile sensibility. Tremor. Affection of the bone marrow. Affection of the endocrine system. Weakening of the immune system.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (alcohol-resistant). Water spray if puddle cannot expand.

Unsuitable extinguishing media

: Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: DIRECT FIRE HAZARD: Highly flammable liquid and vapour. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD: May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

: DIRECT EXPLOSION HAZARD: Gas/vapour explosive with air within explosion limits. Explosion hazard

INDIRECT EXPLOSION HAZARD: may be ignited by sparks. Reactions with explosion

hazards: see "Reactivity Hazard".

Hazardous decomposition products in case of fire

: Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Do not move the load if

exposed to heat.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces:

compressed air apparatus.

Emergency procedures : Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close

doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers

closed. Wash contaminated clothes.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

: Contain released product, pump into suitable containers. Plug the leak, cut off the supply. For containment

Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over

spills.

Methods for cleaning up : Take up liquid spill into a non combustible material e.g.: sand, earth, vermiculite,

kieselguhr, powdered limestone. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and

equipment after handling.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

: Use spark-/explosionproof appliances and lighting system. Take precautions against Precautions for safe handling

electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Keep container tightly closed.

: Observe normal hygiene standards. Hygiene measures

7.2. Conditions for safe storage, including any incompatibilities

: KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources. Heat and ignition sources

Information on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents. (strong) acids. water/moisture.

: Keep out of direct sunlight. Store in a dry area. Ventilation at floor level. Fireproof Storage area

storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills.

Provide the tank with earthing. Meet the legal requirements.

: SPECIAL REQUIREMENTS: closing. dry. clean. correctly labelled. meet the legal Special rules on packaging

requirements. Secure fragile packagings in solid containers.

Packaging materials : SUITABLE MATERIAL: stainless steel. aluminium. iron. copper. nickel. synthetic material.

alass.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol, abs. 100%, HPLC grade (64-17-5)					
Belgium	Limit value (mg/m³)	1907 mg/m³			
Belgium	Limit value (ppm)	1000 ppm			

Ethanol, abs. 100%, HPLC grade Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full face mask with filter type A at conc. in air > exposure limit

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830					
Ethanol, abs. 100%, HPL	.C grade (64-17-5	5)			
France	VME (mg/m³)		1900 mg/m³		
France	VME (ppm)		1000 ppm		
France	VLE (mg/m³)		9500 mg/m³		
France	VLE (ppm)		5000 ppm		
Netherlands	Grenswaarde TO	GG 8H (mg/m³)	260 mg/m³		
Netherlands	Grenswaarde TO	GG 8H (ppm)	136 ppm		
Netherlands	Grenswaarde To	GG 15MIN (mg/m³)	1900 mg/m³		
Netherlands	Grenswaarde To	GG 15MIN (ppm)	992 ppm		
United Kingdom	WEL TWA (mg/n	n³)	1920 mg/m³		
United Kingdom	WEL TWA (ppm)		1000 ppm		
USA - ACGIH	ACGIH STEL (pp	om)	1000 ppm		
Ethanol, abs. 100%, HPL	.C grade (64-17-5	5)	'		
DNEL/DMEL (Workers)		,			
Acute - local effects, inhalatio	on	1900 mg/m³			
Long-term - systemic effects,	dermal	343 mg/kg bw/day			
Long-term - systemic effects,	inhalation	950 mg/m³			
DNEL/DMEL (General popu	lation)	-			
Acute - local effects, inhalatio	on	950 mg/m³			
Long-term - systemic effects,	oral	87 mg/kg bw/day			
Long-term - systemic effects,	inhalation	114 mg/m³			
Long-term - systemic effects,	dermal	206 mg/kg bw/day			
PNEC (Water)					
PNEC aqua (freshwater)		0.96 mg/l			
PNEC aqua (marine water)		0.79 mg/l			
PNEC (Sediment)					
PNEC sediment (freshwater)		3.6 mg/kg dwt			
PNEC sediment (marine water	er)	2.9 mg/kg dwt			
PNEC (Soil)					
PNEC soil		0.63 mg/kg dwt			
PNEC (STP)					
PNEC sewage treatment plar	nt	580 mg/l			
8.2. Exposure controls					
Materials for protective clot	thing:				
GIVE EXCELLENT RESISTANCE: butyl rubber. viton. GIVE GOOD RESISTANCE: neoprene. tetrafluoroethylene. GIVE LESS RESISTANCE: nitrile rubber. polyethylene. GIVE POOR RESISTANCE: natural rubber. PVA. PVC					
Hand protection:					
Gloves					
Eye protection:					
Safety glasses					
Skin and body protection:					
Protective clothing					
Respiratory protection:					
Full face mask with filter type	Full face mask with filter type A at cone in air > expecure limit				

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Molecular mass : 46.07 g/mol
Colour : Colourless.

Odour : Alcohol odour. Pleasant odour.

Odour threshold : No data available pH : 7 (789 g/l, 20 °C)

Relative evaporation rate (butylacetate=1) : 2.4
Relative evaporation rate (ether=1) : 8.3

 $\begin{tabular}{lll} Melting point & : -114 \ ^{\circ}C \ (1 atm) \\ Freezing point & : No data available \\ Boiling point & : 78 \ ^{\circ}C \ (1013 \ hPa) \\ \end{tabular}$

Flash point : 13 °C (Closed cup, 1 atm)

Critical temperature : 243 $^{\circ}$ C Auto-ignition temperature : 363 $^{\circ}$ C

Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : 59 hPa (20 °C)
Vapour pressure at 50 °C : 300 hPa
Critical pressure : 63840 hPa
Relative vapour density at 20 °C : 1.6
Relative density : 0.79 (25 °C)

Relative density of saturated gas/air mixture : 1.04

Density : 786 kg/m³ (25 °C)

Solubility : Soluble in water. Soluble in ether. Soluble in acetone. Soluble in chloroform. Soluble in

oils/fats. Soluble in methanol. Soluble in acids.

Water: 789 g/l (20 °C)
Ether: complete
Acetone: complete

Log Pow : -0.31 (Experimental value)
Viscosity, kinematic : 1.082 mm²/s (40 °C)
Viscosity, dynamic : 1.26 mPa.s (20 °C)
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : 3.3 - 19.0 vol %

67 - 290 g/m³

Lower explosive limit (LEL) : 3.3 vol %
Upper explosive limit (UEL) : 19 vol %

9.2. Other information

Specific conductivity : 135000 pS/m (25 °C)

Other properties : Gas/vapour heavier than air at 20°C. Clear. Hygroscopic. Volatile. Neutral reaction.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with many compounds e.g.: with (strong) oxidizers: (increased) risk of fire/explosion. Reacts violently with many compounds e.g.: with (strong) oxidizers: (increased) risk of fire/explosion. Violent to explosive reaction with (some) acids.

10.2. Chemical stability

Hygroscopic.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10/31/2018 (Version: 1.0) EN (English) 5/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicolo	gical information
-----------------------------	-------------------

1	ľ	K	I.I	ln	fo	rn	na	ti	OI	n	0	n	t	O	χi	ic	0	lo	a	ic	a	e	١fi	fe	ct	S
		-	-		•	ш	-		•		_			•	•	•	•		•	•••	-		44		••	•

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethanol, abs. 100%, HPLC grade (64-17-5)	
LD50 oral rat	10740 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit, Literature study, Dermal)
LC50 inhalation rat (mg/l)	117 - 125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value, Inhalation)
01: " " "	N. () 20 1

Skin corrosion/irritation : Not classified

pH: 7 (789 g/l, 20 °C)

Serious eye damage/irritation : Not classified

pH: 7 (789 g/l, 20 °C)

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Ethanol, abs. 100%, HPLC grade (64-17-5)

Viscosity, kinematic 1.082 mm²/s (40 °C)

Potential adverse human health effects and

symptoms

: Produces effects on the nervous system. Non-toxic if swallowed (LD50 oral, rat > 5000 mg/kg). Non-toxic in contact with skin (LD50 skin> 5000 mg/kg). Slightly irritant to skin. Practically non-toxic by inhalation (LC50 inh, rat > 20 mg/l/4h). Slightly irritant to respiratory organs. Moderately irritant for eyes. Caution! Substance is absorbed through the skin.

SECTION 12: Ecological information

1	2	.1	Т	O	X	C	it۱	V

Ecology - general : Not classified as dangerous for the environment according to the criteria of Regulation (EC)

No 1272/2008

Ecology - air : Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014).

Photolysis in the air. Not classified as dangerous for the ozone layer (Regulation (EC) No

1005/2009)

Ecology - water : Not harmful to crustacea. Not harmful to fishes. No inhibition of activated sludge. Slightly

harmful to algae. Not harmful to bacteria. Harmful to plankton.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

Ethanol, abs. 100%, HPLC grade (64-17-5)	
LC50 fish 1	14200 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 72h algae (1)	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)

12.2. Persistence and degradability

izizi i didictorico aria degradability					
Ethanol, abs. 100%, HPLC grade (64-17-5)					
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.				
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O ₂ /g substance				
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance				
ThOD	2.1 g O ₂ /g substance				
BOD (% of ThOD)	0.43				

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.3. Bioaccumulative potential				
Ethanol, abs. 100%, HPLC grade (64-17-5)				
BCF fish 1 1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)				
Log Pow -0.31 (Experimental value)				
Bioaccumulative potential	Not bioaccumulative.			
12.4. Mobility in soil				
Ethanol, abs. 100%, HPLC grade (64-17-5)				
Surface tension	0.022 N/m (20 °C)			
Ecology - soil	Highly mobile in soil.			

12.5. Results of PBT and vPvB assessment

Ethanol, abs. 100%, HPLC grade (64-17-5)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Do not discharge into surface water. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Remove to an authorized waste incinerator for solvents with energy recovery. May be discharged to wastewater treatment installation.

Additional information

: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

European List of Waste (LoW) code

: 15 01 10* - packaging containing residues of or contaminated by dangerous substances 07 01 04* - other organic solvents, washing liquids and mother liquors

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG IATA ADN RID					
14.1. UN number						
1170	1170	1170	1170	1170		
14.2. UN proper shippin	g name					
ethanol (ethyl alcohol)	ethanol (ethyl alcohol)	Ethanol	ethanol (ethyl alcohol)	ethanol (ethyl alcohol)		
Fransport document description						
UN 1170 ethanol (ethyl alcohol), 3, II, (D/E)				UN 1170 ethanol (ethyl alcohol), 3, II		
14.3. Transport hazard	class(es)					
3	3	3	3	3		
3	3	3	3	3		
14.4. Packing group						
II	II	II	II	II		
14.5. Environmental haz	ards					
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	environment : No environment : No environ		Dangerous for the environment : No		
No supplementary information	n available					

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

Overland transport

Transport regulations (ADR) : Subject to the provisions

: F1 Classification code (ADR) Hazard identification number (Kemler No.) : 33

Orange plates

33 1170

Tunnel restriction code (ADR) : D/E FAC code •2YF

Transport by sea

Transport regulations (IMDG) : Subject to the provisions

: F-E EmS-No. (Fire) EmS-No. (Spillage) : S-D

Air transport

Transport regulations (IATA) : Subject to the provisions

Inland waterway transport

Classification code (ADN) · F1 Carriage permitted (ADN) : T

Rail transport

Transport regulations (RID) : Subject to the provisions

Classification code (RID)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Ethanol, abs. 100%, HPLC grade is not on the REACH Candidate List Ethanol, abs. 100%, HPLC grade is not on the REACH Annex XIV List

VOC content : 100 %

Directive 2012/18/EU (SEVESO III)

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 1, low hazard to water (Classification according to AwSV; ID

No. 96)

12th Ordinance Implementing the Federal

Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

: 5.2.5 Organic Substances

Netherlands

SZW-lijst van kankerverwekkende stoffen : ethanol is listed

SZW-lijst van mutagene stoffen : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

: ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Vruchtbaarheid

: ethanol is listed

NIET-limitatieve lijst van voor de voortplanting

: ethanol is listed

giftige stoffen - Ontwikkeling

Denmark

Class for fire hazard : Class I-1 Store unit

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids

must be followed

15.2. Chemical safety assessment

No additional information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:				
Flam. Liq. 2	Flammable liquids, Category 2			
H225	Highly flammable liquid and vapour.			

SDS Zonder Big

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product